

XEROX®



Technology | Document Management | Consulting Services

EFI® Fiery® Network Colour Server

Simply superb colour printing





EFI® Fiery® Network Colour Server on the Xerox DocuColor 242 / 252 / 260

With the EFI Fiery Network Colour Server on your Xerox DocuColor 242 / 252 / 260 printer-copier, you can count on world-class colour and superior workflow. Here are some of the features and benefits you'll enjoy:

- ColorWise® provides outstanding colour management tools for producing precise, exact colour from all applications, platforms and formats
- Command WorkStation® 4.5 makes it easy to program, monitor and manage workflows
- Variable data printing capabilities enable you to customise your output to a specific audience with varying text, photos and graphics
- EFI Fiery Scan allows you to convert hard copy documents into digital data that you can print, integrate into another document, email or convert into multiple file formats
- Fiery Driver 3.0 based booklet creation for in-line Saddle Stapling, Perfect and Gang-Up for off-line finishing

PRINTER-COPIER SUPPORTED

- DocuColor 242 / 252 / 260

PROCESSOR

- Intel® Celeron® 2.8 GHz

MEMORY

- 512 MB

HARD DISK DRIVE

- 80 GB

CONTROLLER OPERATING SYSTEM

- Linux

NETWORK CONNECTIVITY

- Ethernet 10/100/1000 Base-T Autosensing

PAGE DESCRIPTION LANGUAGES

- Adobe® PostScript® 3™ (v3017)
- PCL 6C (emulation)

PRINT SPECIFICATIONS

Print resolution

- 2400 x 2400 dpi

Pages per minute

- Up to 40 ppm colour, 55 ppm black and white (DocuColor 242)
- Up to 50 ppm colour, 65 ppm black and white (DocuColor 252)
- Up to 60 ppm colour, 75 ppm black and white (DocuColor 260)

First-print-out time

- As fast as 10.7 seconds colour, 4.3 seconds black and white

SCAN RESOLUTION

- 200 x 200 dpi, 300 x 300 dpi,
400 x 400 dpi, 600 x 600 dpi

MAXIMUM IMAGE SIZE

Print

- Maximum Area – 323 x 480 mm
- Maximum Guaranteed – 317 x 480 mm

Scan

- Maximum Area – 297 x 432 mm
- Maximum Guaranteed – 297 x 432 mm

PRINT DRIVERS

Fiery Driver 3.0 (Bi-Directional) support for:

- Windows® 2000
- Windows® XP
- Windows® 2003 Server
- Windows® Vista
- Mac OS® 10.2.3 and later

DRIVER CERTIFICATION

- WHQL Certified

FIERY UTILITIES

(enabled on PC and Apple Operating systems)

- Command WorkStation 4.5
- EFI ColorWise Pro Tools
- Fiery WebTools
- Fiery Remote Scan
- FreeForm for Variable Data Printing
- Spot-On Colour
- Auto Trapping

CALIBRATION

- ColorCal® (standard)
- X-Rite® DTP 32 Series II Densitometer (optional)
Also supports X-Rite DTP41/34 and ES1000

DOCUMENT MANAGEMENT

- RIP while print
- Continuous Print
- Face-up and Face-down printing
- Fiery Scan and Scan-to-Job templates
- Fiery Driver 3.0 based booklet creation

STANDARD COLOUR PROFILES

- SWOP-Coated
- ISO-Coated
- ISO-Uncoated
- DIC
- Euroscale
- TOYO Offset Coated 2.0

FONTS

- 136 Adobe fonts
- 80 PCL 6C (emulation) fonts

OPTIONS

- X-Rite DTP 32 Series II Densitometer
- Secure Disk Erase
- EFI Profiler 2.0
- Impose 2.7
- 512 MB memory upgrade
- Splash RPX-ii
- Hot Folders / Virtual Printers (standard on DocuColor 260)
- Scan to PC Desktop®

SECURITY

- Secure Disk Erase (option)
- Scan to mailbox
- SNMPv3
- IP Sec
- 802.1x
- SSL/TLS
- User Authentication
- IP Filtering / Port Blocking
- System Update
- IPv6

POWER REQUIREMENTS

- Controller power supplied by the DocuColor 242 / 252 / 260 engine. No additional power service is required.
220 – 240v – 10 Amp

