

# DocuColor 2006

## PRINTER/COPIER

The Xerox DocuColor 2006 printer/copier gives you top quality prints *and* copies—together in a single, high-performance solution.



Built for colour-intensive environments where image is everything, it is the ultimate printing, copying, proofing and comping tool. It has the range to handle any challenge: copying, two-sided printing, full A3+ page size, and media as varied as heavyweight, coated gloss and transparencies.

Whether you need professional-quality proofs, brochures, posters, presentations or reports, the DocuColor 2006 delivers.



### *need more information?*

Find it at [www.xerox.com/officeprinting](http://www.xerox.com/officeprinting)

See the DocuColor 2006 in action. Visit your Xerox reseller, or go to our web site for a virtual printer/copier demo: [www.xerox.com/officeprinting/2006demo](http://www.xerox.com/officeprinting/2006demo)


Service & Support. Learn about Total Satisfaction Services<sup>SM</sup> award-winning service and support: [www.xerox.com/officeprinting/support](http://www.xerox.com/officeprinting/support)

### *outstanding image quality*

The DocuColor 2006 prints and copies at 600 x 600 dpi resolution enhanced by 8-bit colour depth per pixel for precise continuous-tone quality detail.



Advanced colour matching technology, independent RGB, CMYK and Pantone® colour workflow, and Automatic Pantone® Colour Calibration with embedded colour dictionaries are included for easy and precise colour rendering.



Automatic internal density control assures consistent colour without user intervention. VisualCal print

adjustments and densitometer-based calibration methods are available for more demanding needs.

Xerox patented Intermediate Belt Technology (previously reserved for our highest-end digital presses) guarantees perfect colour registration and paper weight flexibility.

### *advanced performance on your network*

Print and copy at speeds of 6 ppm colour/26 ppm black and white.

The DocuColor 2006 integrates seamlessly onto your network. Parallel and 10/100BaseTX Ethernet are standard.

Powerful embedded 266 MHz controller and standard 64 Mbytes of RAM (expandable to 512 Mbytes).

High duty cycle ensures maximum productivity and easy-to-replace cartridges and waste containers increase uptime.

Advanced technology and simple, modular design make the DocuColor 2006 extremely reliable.

## easy to use print and copy features

At the desktop or at the device, the DocuColor 2006 is intuitive and easy to operate.

Web-based printer administration lets you view job status, manage print queues and access drivers and printer support.

Printing capabilities like Document Set printing, electronic collation, Spool-Hold-Print queues (with thumbnail viewing and editing options) and direct PDF and PostScript downloading streamline your workflow.

Extensive copy features include zoom magnification from 25 to 400%, auto reduction/enlargement, auto document size sensing, auto colour selection and border/centre erase.

## exceptional versatility

Extensive media flexibility lets you print and copy everything in-house. Paper weights from 64 to 220gsm, page size up to A3+ (330 x 457mm).

Fully-integrated copier/ scanner ❶ is easy to use and provides common copying capabilities at your fingertips.

Automatic 2-sided printing option ❷ (standard on the 2006DPC) makes brochure printing fast and easy.



Standard paper capacity of 250-sheet universal tray ❸, 150-sheet bypass tray ❹ and 2-tray 1,000-sheet high-capacity feeder ❺ for a total of 1,400 sheets.

Automatic Document Feeder ❻ (standard on the 2006DPC) adds productivity and flexibility.

Optional Sorter/Stacker ❼ collates jobs for easy pick-up and distribution-ready documents.





DocuColor 2006DPC configuration includes: a copier/scanner, 128 MB RAM, automatic 2-sided printing, internal hard disk, 1,000-sheet high capacity feeder, automatic document feeder and optional 10-bin sorter/stacker.

**XEROX**  
NETWORK PRINTERS

# DOCUCOLOR 2006 COLOUR PRINTER/COPIER SPECIFICATIONS




## Media and Accessories




## Configurations

		
	2006NPC	2006DPC
Print/copy speed	6 ppm colour / 26 ppm black and white	
First page out	print: 26 seconds colour / 11 seconds black and white copy: 31 seconds colour / 11 seconds black and white	
Image processing	266-MHz R5271 MIPS processor, Adobe PostScript 3	
Memory Standard / Maximum	64 MB / 512 MB RAM	128 MB / 512 MB RAM
Print/copy resolution	600 x 600 dpi x 8 bit colour depth per pixel	
Maximum page size	A3+ (330 x 457mm/13 x 18in)	
Network connectivity	10/100BaseTX Ethernet, Bi-directional parallel	
Paper input capability	1,400 sheets	
Monthly duty cycle	up to 65,000 pages/month / Average monthly print volume 2,000 to 5,000	
Standard features	Copier/scanner 2 Tray High Capacity Feeder 6 GB Internal hard disk	Copier/scanner 2 Tray High Capacity Feeder 6 GB Internal hard disk Automatic 2-sided printing Automatic Document Feeder
Optional accessories	Automatic 2-sided printing Token Ring, Dedicated Transparency Tray Automatic Document Feeder, 10-Bin Sorter/Stacker Oversize tray	Token Ring Dedicated Transparency Tray 10-Bin Sorter/Stacker Oversize tray
Customer support	Warranty plus service options, online technical support, telephone support, colour printing newsletter	

- Xerox Phaser Professional Printing Paper
  - Phaser Premium Colour Printing Paper (90gsm) A4, A3, SRA3, US Letter, 11 x 17 in, 12 x 18 in
  - Phaser Premium Cover Paper (160gsm) A4, US Letter
  - Premium Coated Cover Paper (160gsm) 12 x 18 in
  - Phaser Glossy Coated Paper (148gsm) A4, A3, SRA3, US Letter, 11 x 17 in, 12 x 18 in
  - Premium Transparency Film A4, US Letter
- Accessories
- Oversize Paper Tray (250 sheets)
  - Transparency Tray (250 sheets)
  - Automatic Duplex Unit
  - Automatic Document Feeder
  - 10-Bin Sorter/Stacker
  - Densitometer
  - Token Ring
  - Additional Memory  
64 MB, 128 MB, 256 MB, 512 MB

## Specifications


<b>Network/Software</b>
Printer management Hold Queue, Print Queue, Direct Queue, RIP while print, Continuous print, Electronic collation, Document set printing, Reverse order printing, Maximum print quantity, Job log, Billing meter, Job recovery, Cancel job, PS and PDF File downloading
Font capabilities 138 PostScript fonts, 1 Bitmap, 10 TrueType, 35 Intellifonts
Printer drivers Windows 95/98, Windows NT 4.0, Windows 2000, Mac OS 8.x, OS 9.x
Languages Genuine Adobe® PostScript® 3™, Colour PCL 5c emulation with automatic sensing and switching

<b>Paper Handling</b>
Media input trays standard 250 sheet universal tray, 150 sheet bypass tray and 2-tray 1,000 sheet high-capacity feeder
Media types 64–220 gsm (16–110 lb. index) cover stock, coated or glossy papers, Xerox-branded transparencies, laser-quality labels, envelopes, recycled paper, business cards
Media sizes Minimum: 90 x 139.7mm (3.5 x 5.5in) Maximum: 330.2 x 457.2mm (13 x 18in) Maximum image size: 320 x 447mm (12.6 x 17.7in)

<b>Special Features</b>
Document Management Document Set printing, PDF Direct printing, Concurrent Job Receiving, RIP Once/Print Many, RIP while printing
Web tools PDF, PS, Remote machine status, Web setup tools, installation tools


<b>Copy Features</b>
Copier/scanner Up to 99 copies per job, Zoom magnification from 25 to 400%, Auto reduction/enlargement, Auto document size sensing, Auto colour selection, Border/centre erase, Two in one, 600 x 600 x 8 bit depth scan resolution, optional document feeder

<b>Colour Controls</b>
Colour matching PANTONE®-approved solid-colour simulations, ICC, ICM, ColorSync, custom ICC
Colour standards SWOP, EuroScale, DIC
Rendering Styles Photographic, Business graphics, Absolute and Relative Colorimetric

<b>Operating</b>
Dimensions Width: 650mm/25.6in, Height: 1160mm/46in, Depth: 749mm/29.5in, Weight: 72kg/159lb, Scanner: 25kg/55lb, ADF: 22kg/49lb, Scanner stand: 35kg/77lb
Environment Temperature: Storage: -20° to 40°C (-4° to 104°F), Operating: 5° to 32°C (41° to 89.6°F). Relative Humidity: Storage: 5% to 85%, Operating: 15% to 85%. Altitude: 0–3100m (0–10,107ft) PQ guaranteed
Electrical Models: 200–260 VAC, 50/60 Hz, 110–130 VAC, 50/60 Hz, Consumption: warm-up 100W, continuous printing 1100W or less, idle 250W or less, Energy Star 45W or less
Regulatory FCC Part 15, Subpart B, CE Mark applicable to directives 73/23/EEC, 93/68/EEC and 89/336/EEC

Australia Tel.: 1-300-369-519 Tech Sup: 1-800-811-177 China Tel.: 10 6235 1210 India/South Asia Tel.: +91 80 227 5577 Japan Tel.: (3) 3448-3028 Korea Tel.: 2 528 5808-9  
 Malaysia Tel.: 3 246 2433 New Zealand Tel.: 0800-449-177 Hong Kong Tel.: 2513-2513 Singapore/ASEAN Tel.: +65 251 3006 Taiwan Tel.: 2 2722 9622 Thailand Tel.: (2) 645-4406  
 Toronto Tel.: (416) 747-5000 United Kingdom Tel.: 0870 241 3245

[www.xerox.com/officeprinting](http://www.xerox.com/officeprinting)



XEROX®, The Document Company® and the digital X®, and DocuColor are trademarks of XEROX CORPORATION. Windows 95/98/2000, NT and the Microsoft logo are trademarks of Microsoft Corporation. AppleTalk is a trademark of Apple Computer, Inc. ColorWise® and the Fiery logo are trademarks of Electronics for Imaging, Inc. Adobe, PostScript and the Adobe PostScript logo are trademarks of Adobe Systems, Inc. Novell IPX/SPX, NetWare and the NetWare logo are trademarks of Novell, Inc. In support of Xerox' environmental leadership goals, products are either newly manufactured or manufactured and contain both new components and reprocessed components that are reconditioned. Product appearance, and/or specifications are subject to change without notice. Copyright 2001 © XEROX CORPORATION. All rights reserved. 03/01

DIGITAL  
**THE DOCUMENT COMPANY**  
**XEROX**

DC6BR-01EA



DOCUCOLOR 2006  
PRINTER/COPIER

When Image is  
**Everything**



**XEROX**  
NETWORK PRINTERS

