

WorkCentre® 6400

Colour Multifunction Printer



WorkCentre 6400S
A full-featured multifunction printer with automatic 2-sided print/copy/scan capabilities



WorkCentre 6400X
All of the features of the 6400S plus faxing capabilities



WorkCentre 6400XF
Adds 2 input paper trays, finishing and a stand

	WorkCentre 6400S	WorkCentre 6400X	WorkCentre 6400XF
Output Speed			
Black and White	Up to 35 ppm A4 Up to 30 ppm 216 x 356 mm		
Colour	Up to 30 ppm A4 Up to 26 ppm 216 x 356 mm		
Paper Handling – Input			
Duplex Automatic Document Feeder			
Capacity¹	50 sheets		
Sizes	Custom Sizes: 148 x 210 mm to 216 x 356 mm		
Weights	50 to 105 gsm		
Multipurpose Tray 1			
Capacity¹	100 sheets		
Sizes	Custom Sizes: 97 x 147 mm to 216 x 356 mm		
Weights	60 to 210 gsm		

¹ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

Media Types	Plain paper Bond Letterhead Envelopes Labels Transparencies Postcard Recycled Punched Pre-printed Heavyweight (91 - 150 gsm) Extra Heavyweight (151 - 210 gsm) Gloss (100 - 128 gsm) Heavyweight Gloss (129 - 210 gsm)
Tray 2 (Standard)	
Capacity¹	500 sheets
Sizes	A4
Weights	60 to 90 gsm
Media Types	Plain paper Bond Letterhead Recycled Punched Pre-printed Archive
Trays 3 and 4 (Standard on 6400XF)	
Capacity¹	500 sheets each
Sizes	A4, B5
Weights	60 to 90 gsm
Media Types	Plain paper Bond Letterhead Recycled Punched Pre-printed Archive
Paper Handling – Output	
Standard Output	500 sheets; automatic 2-sided
Finishing (Standard on 6400XF)	Stapling: 30 sheets
Print	
First-Page-Out-Time	As fast as 16 seconds
Print Resolution	Up to 2400 x 600 dpi
Memory (Std/max)	1 GB

¹ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

WorkCentre 6400

Processor	800 MHz
Hard Disk Drive	80 GB
Language Support	Adobe® PostScript® 3™ PCL® 5c PCL® 6 PDF 1.6 TIFF JPEG
Connectivity	USB 2.0 (for print only); 10/100/1000 Base-TX Ethernet IPv4 and IPv6
Printing Features	Automatic 2-sided Custom page size N-Up Banner sheet Inserts, Covers Booklet creation Mirror image Collation Watermarks Scaling Print Around Sample set Secure print Delayed print Saved print job
Print Drivers	Microsoft® Windows® 2000/2003/XP/Vista Mac OS® X version 10.3 and higher Linux® Turbolinux® 10 Desktop SUSE™ Red Hat® Xerox Global Print Driver™ Xerox Mobile Express Driver™
Font Capability	141 PostScript® fonts 81 PCL® fonts
Copy	
Document Scanner	Duplex Automatic Document Feeder with 50-sheet capacity
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 999
Resolution	600 x 600 dpi
Concurrency	Concurrent scanning and printing
First-Copy-Out-Time	As fast as 18 seconds

Copy Features	Automatic 2-sided Collation Reduce/enlarge 25 to 400 % Lighten/darken Booklet creation Covers Inserts Annotations Bates Stamping Transparency separators Multiple-up Build Job Sample copy Save copy settings
Fax (Available on 6400X and 6400XF)	
Embedded Fax, LAN Fax, Internet Fax, Network Server Fax Enablement	
Fax Speed	33.6 Kbps
Memory	Uses device memory
Resolution	Up to 300 x 300 dpi (superfine) resolution
Compression	MH, MR, MMR
Fax Features	Junk fax filter Mailboxes and Polling Secure Fax Delayed Send Speed dials (up to 200) Group dials
Scan	
Capability	Black and white and colour scanning
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring Scan to network or fax jobs
Input Speed	Black and white: Scan up to 35 ipm (A4) Colour: Scan up to 30 ipm (A4)
Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 150 x 150 dpi 100 x 100 dpi 72 x 72 dpi
Maximum Scan Area	216 x 356 mm
Network Protocol	FTP HTTP HTTPS SMB

File Formats	PDF Searchable PDF TIFF Multipage TIFF JPEG
Supported Scan Destinations	Scan to Mailbox Scan to Email Scan to File Scan to Home
Scanning Solutions	
Scan to PC Desktop® Personal Edition (1 Seat)	A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools <ul style="list-style-type: none"> • ScanSoft PaperPort – image viewing and file management software • ScanSoft OmniPage (for desktop/client installation) – OCR and file format conversion software • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops
Accounting	
Accounting Control	
	Xerox Standard Accounting Job based accounting Network Accounting enablement
Xerox Standard Accounting	
Tracking	Copy, Print, Fax and Scan usage
Accounting	Up to 2,499 User accounts Up to 500 General accounts Up to 499 Group accounts
Features	Enable/disable via the web UI or the GUI in tools; admin can manage the feature remotely via the web UI; data can be exported via a CSV file; user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.
Security	
Security Features	Disk Overwrite Job Overwrite Disk encryption 802.1X Secure Print Authentication Secure Fax
Device Management	
Xerox CentreWare® Web	
	<ul style="list-style-type: none"> • A web-based server application for network administrators that permits web browser-based device management from any workstation, running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks, troubleshooting, device upgrades and basic accounting and asset management

Xerox CentreWare® Internet Services – Integrated Device Web Page

Device Status	Web server embedded <ul style="list-style-type: none"> • Tray status/contents • Consumables status
Print Queue Viewing	Complete job print queue management – hold, release, promote and delete
Job Submission	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection
Device Administration	Allows simple, remote installation setting of configuration options and device management
Browsers	Windows® XP, Netscape Navigator®, Firefox® Microsoft® Internet Explorer Macintosh® 9.x/OS X: Netscape Navigator® 6.x, Apple® Safari™, Firefox® Linux: Netscape® 6.x

Xerox Extensible Interface Platform™ (EIP)

Xerox Extensible Interface Platform (EIP) is an embedded software platform built with state-of-the-art web technologies. This platform provides the means for software developers to quickly build solutions that are more intuitive and user-friendly for office workers. Chief among the capabilities provided by EIP is the development of tailored applications with customised user interfaces, and card-based authentication solutions supporting a personalised user experience.

Device Specifications

Duty Cycle

Up to 120,000 pages per month*

Recommended Monthly Print Volume

Up to 15,000 pages per month**

Power Consumption

Printing	802 watts
Standby	161 watts
Power Save	26 watts
Warm Up (from power save)	First Print: As fast as 60 seconds User Interface ready and programmable: 5-6 seconds
Warm Up (from power on)	First Print: As fast as 5 minutes (maximum) User Interface ready and programmable: As fast as 4 minutes (maximum)
Operating Temperature Range	10° to 32° C
Storage Temperature Range	-20° to 40° C
Maximum Humidity Range	15 % to 85 %
Storage Humidity Range	10 % to 95 %

*Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis

**Range reflects the number of pages per month the product can regularly print while maintaining optimal performance (considering factors including supplies replenishment and reliability over the expected product life).

WorkCentre 6400

Dimensions and Weights	Width	Depth	Height	Weight
6400S/6400X	530 mm	588 mm	627 mm	59 kg
6400XF	1,008 mm	673 mm	1169 mm	110 kg
Package Dimensions	Width	Depth	Height	Weight
6400S/6400X	760 mm	650 mm	883 mm	69 kg
6400XF	1118 mm	770 mm	1458 mm	152 kg
Clearance Requirements				
<ul style="list-style-type: none"> • A minimum of 267 mm is required between the wall and the back of the unit. • Service access/installation requires a minimum width of 1296 mm for a WorkCentre 6400 without a finisher (6400S/6400X) and 1396 mm for a WorkCentre 6400 with a finisher (6400XF). A minimum depth of 780 mm is required. 				
Certifications				
FCC Part 15, Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC Listed UL 60950-1/CSA 60950-1-03				
What Comes in the Box				
WorkCentre 6400 Toner cartridges (8,000 print capacity ¹ for CMY and 12,000 print capacity ¹ for Black) Software (Scan to PC Desktop SE Personal Edition with one license for OmniPage and PaperPort) Documentation CD (with User Manual, Quick Installation Guide and Warranty Statement) Fax cord and power cord				
Supplies and Options	Description	Order Number		
Print cartridges ¹	Cyan standard-capacity: 8,000 pages	106R01320		
	Magenta standard-capacity: 8,000 pages	106R01321		
	Yellow standard-capacity: 8,000 pages	106R01322		
	Black high-capacity: 12,000 pages	106R01316		
	Cyan high-capacity: 16,500 pages	106R01317		
	Magenta high-capacity: 16,500 pages	106R01318		
	Yellow high-capacity: 16,500 pages	106R01319		
Staple cartridges	Staple cartridge (Qty 3): 5,000 each	108R00813		
Imaging Units ²	Cyan Imaging Unit: 30,000 pages	108R00775		
	Magenta Imaging Unit: 30,000 pages	108R00776		
	Yellow Imaging Unit: 30,000 pages	108R00777		
	Black Imaging Unit: 30,000 pages	108R00774		
Routine Maintenance	Waste cartridge (Qty 2): 22,000 pages	106R01368		
	220V Fuser: 150,000 pages	115R00060		
	Transfer Roller: 120,000 pages	108R00815		
	Transfer Belt: 120,000 pages	108R00816		
	ADF Roller Kit: 100,000 pages	108R00866		

¹ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.s

² Approximate pages. Declared Yield based on an average job of 5 pages, A4 size. Yield will vary based on job run length, media size and orientation.

WorkCentre 6400

Supplies Recycling Programme

Consumables for the WorkCentre 6400 are part of the Xerox Green World Alliance Supplies Recycling Programme.

For more information, please visit the Green World Alliance website at www.xerox.com/gwa.

